

Phottix®

PHOTOLEX®

Helios 2077

MOBILE RGB LED LIGHT



Features



Maximum brightness of 15W output

Type-C 5V/3A, 9V/2A 20W input

Excellent color rendering – CRI 96+ (TLCI 98+)

Wide range of color temperature 2500K – 9900K

0-360° full color and saturation adjustment (HSI)

21 present scenario effects

Use as a power bank to charge other devices

Smartphone APP via bluetooth remote control

Long-life, Low-Heat LEDs

Long-Life Built-In Battery

Adjustable brightness and color temperature via double Aluminum alloy knob

Compact size – 23mm thick



15W
MAX. POWER



RGB
MULTI-COLORS



HSI



21 SCENARIO
EFFECTS



CCT




2500K-9900K
COLOR TEMP.




Allows charge your electronic devices



Adjustable brightness and color temperature via double Aluminum alloy knob



CCT mode



HSI mode



Scene mode

Technical Specs

SKU / Model:	Helios 2077 Mobile RGB LED light
Color temperature:	2500-9900K
Color model:	0-360° full color control (HSI)
Scenario effects:	21 present
Brightness range:	0% - 100%
Max. brightness / illuminance:	1818 lux (@5600K 0.5m)
Max. Power:	15W
Color rendering index:	CRI96+ / TLCI 95+
Battery capacity:	3.7V 10000mAh
Control method:	Via Device / Via Bluetooth APP
Connectors:	Type-C x 1, USB x 1, 1/4" Thread insert x 3
Input Power:	5V/3A, 9V/2A 20W Max.
Output Power:	5V/3A
Dimension:	159 x 79 x 23mm
Weight:	390 g

*Product Photo and Specification Data for reference only, product in kind prevail.

What's included

Helios 2077 mobile RGB LED light • Silicone diffuser • Barndoors • Grid • Cold Shoe Adaptor Pouch Bag • 1/4" Locking Knob x 2 • 1m Type-C Charging Cable • User Manual



Phottix.com | Sale@phottix.com
tel: +852 2575 0739

Contact Persons
Ms. Jean Lo / Mr. Ma

PhottixHQ

PhottixPPA
PhottixHongKong